



US009636755B2

(12) **United States Patent**  
**Grosbois et al.**

(10) **Patent No.:** **US 9,636,755 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **TOOL FOR MACHINING A WALL OF A WORKPIECE, IN PARTICULAR MADE FROM A COMPOSITE MATERIAL**

(58) **Field of Classification Search**  
CPC . B23G 1/38; B23G 5/00; B23G 5/005; B23G 2200/28; B23G 2200/32;  
(Continued)

(71) Applicant: **SNECMA**, Paris (FR)

(56) **References Cited**

(72) Inventors: **Christophe Grosbois**, Combs la Ville (FR); **Mathias Seve**, Paris (FR)

U.S. PATENT DOCUMENTS

(73) Assignee: **SNECMA**, Paris (FR)

559,372 A \* 5/1896 Elterich ..... B23G 5/06  
408/218  
1,265,348 A \* 5/1918 Lloyd ..... B23G 5/06  
33/555.2

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 131 days.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/369,797**

CN 1753751 A 3/2006  
CN 1754641 A 4/2006  
(Continued)

(22) PCT Filed: **Jan. 3, 2013**

(86) PCT No.: **PCT/FR2013/050012**

§ 371 (c)(1),

(2) Date: **Jun. 30, 2014**

OTHER PUBLICATIONS

International Search Report Issued Apr. 23, 2013 in PCT/FR13/050012 Filed Jan. 3, 2013.

(87) PCT Pub. No.: **WO2013/102736**

PCT Pub. Date: **Jul. 11, 2013**

*Primary Examiner* — Eric A Gates

*Assistant Examiner* — Paul M Janeski

(65) **Prior Publication Data**

US 2014/0363246 A1 Dec. 11, 2014

(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.

(30) **Foreign Application Priority Data**

Jan. 5, 2012 (FR) ..... 12 50136

(57) **ABSTRACT**

(51) **Int. Cl.**  
**B23G 5/06** (2006.01)  
**B23B 51/02** (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **B23B 51/02** (2013.01); **B23B 35/00** (2013.01); **B23G 1/38** (2013.01); **B23G 5/00** (2013.01);

(Continued)

A tool for machining a wall of a workpiece, made from a composite material, that can cut a groove in the wall, the tool including a head mounted integrally with a rod having a longitudinal axis and capable of being driven in rotation about the longitudinal axis. The head includes at least one main protruding annular rib with an outer surface covered with abrasive grains of predetermined particle size and with a radial height corresponding to the depth of the groove to be cut, and at least one auxiliary protruding annular rib with an outer surface covered with abrasive grains of predetermined particle size and with a radial height less than the radial height of a main rib. The auxiliary rib includes two

(Continued)

